

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 3225-0273:104 Page 1 of 1

CATEGORY: Fire Dampers

LISTEE: United Air, PO Box 40913, Nashville TN 37204
Contact: *Jon Newnam (615) 256-3500

DESIGN: Models U-305 and U-315 curtain type fire dampers. No. 18 to 22 Ga. galvanized steel frame, No. 22 Ga. galvanized steel blades construction. Refer to listee's data sheet for additional detailed product description and operational considerations.

Model	Single Section		Multiple Assemblies	
	<u>Width</u>	<u>Height</u>	<u>Width</u>	<u>Height</u>
U-305	36"	36"	NA	NA
U-315	48"	48"	96"	48"

RATING: 1-1/2 Hour

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes & ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, classification and UL label.

APPROVAL: Listed as fire dampers for use in heating, ventilating and air conditioning duct systems passing through fire resistive walls, partitions or floors. Model U-305 is suitable for horizontal and vertical installation. Model U-315 is suitable for vertical installation only.

NOTE: Leakage rating not evaluated. Refer to CSFM Listing Category 3230 for listed leakage dampers.

*Rev. 06-08-2002



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued:

JUNE 8, 2002

*Listing Expires **June 30, 2003***

Authorized By:

DIANE K. AREND, Senior Deputy
Program Manager